
HOUSE BILL 1100

State of Washington

64th Legislature

2015 Regular Session

By Representative Morris

Prefiled 01/09/15.

1 AN ACT Relating to creating new appliance efficiency standards;
2 amending RCW 19.260.030, 19.260.040, and 19.260.050; and reenacting
3 and amending RCW 19.260.020.

4 BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF WASHINGTON:

5 **Sec. 1.** RCW 19.260.020 and 2009 c 565 s 18 and 2009 c 501 s 1
6 are each reenacted and amended to read as follows:

7 The definitions in this section apply throughout this chapter
8 unless the context clearly requires otherwise.

9 (1) "Automatic commercial ice cube machine" means a factory-made
10 assembly, not necessarily shipped in one package, consisting of a
11 condensing unit and ice-making section operating as an integrated
12 unit with means for making and harvesting ice cubes. It may also
13 include integrated components for storing or dispensing ice, or both.

14 (2) "Bottle-type water dispenser" means a water dispenser that
15 uses a bottle or reservoir as the source of potable water.

16 (3) "Commercial hot food holding cabinet" means a heated, fully
17 enclosed compartment, with one or more solid or partial glass doors,
18 that is designed to maintain the temperature of hot food that has
19 been cooked in a separate appliance. "Commercial hot food holding
20 cabinet" does not include heated glass merchandising cabinets, drawer
21 warmers, or cook and hold appliances.

1 (4)(a) "Commercial refrigerators and freezers" means
2 refrigerators, freezers, or refrigerator-freezers designed for use by
3 commercial or institutional facilities for the purpose of storing or
4 merchandising food products, beverages, or ice at specified
5 temperatures that: (i) Incorporate most components involved in the
6 vapor-compression cycle and the refrigerated compartment in a single
7 cabinet; and (ii) may be configured with either solid or transparent
8 doors as a reach-in cabinet, pass-through cabinet, roll-in cabinet,
9 or roll-through cabinet.

10 (b) "Commercial refrigerators and freezers" does not include: (i)
11 Products with 85 cubic feet or more of internal volume; (ii) walk-in
12 refrigerators or freezers; (iii) consumer products that are federally
13 regulated pursuant to 42 U.S.C. Sec. 6291 et seq.; (iv) products
14 without doors; or (v) freezers specifically designed for ice cream.

15 (5) "Compensation" means money or any other valuable thing,
16 regardless of form, received or to be received by a person for
17 services rendered.

18 (6) "Cook and hold appliance" means a multiple mode appliance
19 intended for cooking food that may be used to hold the temperature of
20 the food that has been cooked in the same appliance.

21 (7) "Department" means the department of commerce.

22 (8) "Drawer warmer" means an appliance that consists of one or
23 more heated drawers and that is designed to hold hot food that has
24 been cooked in a separate appliance at a specified temperature.

25 (9) "Heated glass merchandising cabinet" means an appliance with
26 a heated cabinet constructed of glass or clear plastic doors which,
27 with seventy percent or more clear area, is designed to display and
28 maintain the temperature of hot food that has been cooked in a
29 separate appliance.

30 (10) "Hot water dispenser" means a small electric water heater
31 that has a measured storage volume of no greater than one gallon.

32 (11) "Mini-tank electric water heater" means a small electric
33 water heater that has a measured storage volume of more than one
34 gallon and a rated storage volume of less than twenty gallons.

35 (12) "Pass-through cabinet" means a commercial refrigerator or
36 freezer with hinged or sliding doors on both the front and rear of
37 the unit.

38 (13) "Point-of-use water dispenser" means a water dispenser that
39 uses a pressurized water utility connection as the source of potable
40 water.

1 (14) "Pool heater" means an appliance designed for heating
2 nonpotable water contained at atmospheric pressure for swimming
3 pools, spas, hot tubs, and similar applications.

4 (15) "Portable electric spa" means a factory-built electric spa
5 or hot tub, supplied with equipment for heating and circulating
6 water.

7 (16) "Reach-in cabinet" means a commercial refrigerator or
8 freezer with hinged or sliding doors or lids, but does not include
9 roll-in or roll-through cabinets or pass-through cabinets.

10 (17) "Residential pool pump" means a pump used to circulate and
11 filter pool water in order to maintain clarity and sanitation.

12 (18)(a) "Roll-in cabinet" means a commercial refrigerator or
13 freezer with hinged or sliding doors that allow wheeled racks of
14 product to be rolled into the unit.

15 (b) "Roll-through cabinet" means a commercial refrigerator or
16 freezer with hinged or sliding doors on two sides of the cabinet that
17 allow wheeled racks of product to be rolled through the unit.

18 (19) "Showerhead" means a device through which water is
19 discharged for a shower bath.

20 (20) "Showerhead tub spout diverter combination" means a group of
21 plumbing fittings sold as a matched set and consisting of a control
22 valve, a tub spout diverter, and a showerhead.

23 (21) "State-regulated incandescent reflector lamp" means a lamp
24 that is not colored or designed for rough or vibration service
25 applications, has an inner reflective coating on the outer bulb to
26 direct the light, an E26 medium screw base, a rated voltage or
27 voltage range that lies at least partially within 115 to 130 volts,
28 and falls into one of the following categories:

29 (a) A bulged reflector or elliptical reflector bulb shape and
30 which has a diameter which equals or exceeds 2.25 inches; or

31 (b) A reflector, parabolic aluminized reflector, or similar bulb
32 shape and which has a diameter of 2.25 to 2.75 inches.

33 (22) "Tub spout diverter" means a device designed to stop the
34 flow of water into a bathtub and to divert it so that the water
35 discharges through a showerhead.

36 (23) "Wine chillers designed and sold for use by an individual"
37 means refrigerators designed and sold for the cooling and storage of
38 wine by an individual.

1 (24) "À la carte charger" means a battery charger that is
2 individually packaged without batteries. "À la carte charger"
3 includes those with multivoltage or multiport capabilities.

4 (25) "Battery analyzer" means a device:

5 (a) Used to analyze and report a battery's performance and
6 overall condition;

7 (b) Capable of being programmed and performing service functions
8 to restore capability in deficient batteries; and

9 (c) Not intended or marketed to be used on a daily basis for the
10 purpose of charging batteries.

11 (26) "Battery backup" or "uninterruptible power supply charger"
12 means a small battery charger system that is voltage and frequency
13 dependent and designed to provide power to an end-use product in the
14 event of a power outage, and includes an uninterruptible power supply
15 charger as defined in IEC 62040-3 ed.2.0 (March 2011). The output of
16 the voltage and frequency dependent uninterruptible power supply
17 charger is dependent on changes in AC input voltage and frequency and
18 is not intended to provide additional corrective functions, such as
19 those relating to the use of tapped transformers.

20 (27) "Battery charger systems" means a battery charger coupled
21 with its batteries or battery chargers coupled with their batteries,
22 which together are referred to as battery charger systems. This term
23 covers all rechargeable batteries or devices incorporating a
24 rechargeable battery and the chargers used with them. The charging
25 circuitry of battery charger systems may or may not be located within
26 the housing of the end-use device itself. In many cases, the battery
27 may be charged with a dedicated external charger and power supply
28 combination that is separate from the device that runs on power from
29 the battery. Battery charger systems include, but are not limited to:

30 (a) Electronic devices with a battery that are normally charged
31 with AC line voltage or DC input voltage through an internal or
32 external power supply and a dedicated battery charger;

33 (b) The battery and battery charger components of devices that
34 are designed to run on battery power during part or all of their
35 operations;

36 (c) Dedicated battery systems primarily designed for electrical
37 or emergency backup; and

38 (d) Devices whose primary function is to charge batteries, along
39 with the batteries they are designed to charge. These units include
40 chargers for power tool batteries and chargers for automotive, AA,

1 AAA, C, D, or 9 V rechargeable batteries, as well as chargers for
2 batteries used in larger industrial motive equipment and à la carte
3 chargers.

4 (28) "Consumer product" means any article that when operated
5 consumes energy including articles that to any significant extent are
6 distributed in commerce for personal use or consumption by
7 individuals. "Consumer product" does not include an automobile as
8 defined in 49 U.S.C. Sec. 32901(a)(3).

9 (29) "High light output double-ended quartz halogen lamp" means a
10 lamp that:

- 11 (a) Is designed for general outdoor lighting purposes;
- 12 (b) Contains a tungsten filament;
- 13 (c) Has a rated initial lumen value of greater than 6,000 and
14 less than 40,000 lumens;
- 15 (d) Has at each end a recessed single contact, R7s base;
- 16 (e) Has a maximum overall length between four and eleven inches;
- 17 (f) Has a nominal diameter less than 3/4 inch;
- 18 (g) Is designed to be operated at a voltage not less than 110
19 volts and not greater than 200 volts or is designed to be operated at
20 a voltage between 235 volts and 300 volts;
- 21 (h) Is not a tubular quartz infrared heat lamp; and
- 22 (i) Is not a lamp marked and marketed as a stage and studio lamp
23 with a rated life of 500 hours or less.

24 (30) "Illuminated exit sign" means:

- 25 (a) A sign that is designed to be permanently fixed in place to
26 identify an exit; and
- 27 (b) A sign that: (i) Consists of an electrically powered integral
28 light source that illuminates the legend "EXIT" and any directional
29 indicators; and (ii) provides contrast between the legend, any
30 directional indicators, and the background.

31 (31) "Large battery charger system" means a battery charger
32 system, other than a battery charger system for golf carts, with a
33 rated input power of more than two kilowatts.

34 (32) "Small battery charger system" means a battery charger
35 system with a rated input power of two kilowatts or less, and
36 includes golf cart battery charger systems regardless of the output
37 power.

38 (33) "Small diameter directional lamp" means a multifaceted
39 reflector (MR) lamp, a parabolic aluminized reflector (PAR) lamp, a
40 reflector (R) lamp, and a directional light emitting diode

1 replacement lamp that is less than or equal to 2.25 inches in
2 diameter and that includes all wattage, lumen-output, center beam
3 candle power, and color temperature offerings.

4 (34) "State-regulated light emitting diode lamp" or "LED lamp"
5 means any LED lamp that:

6 (a) Produces light within 7 MacAdam steps of the black-body
7 curve;

8 (b) Has an E12, E17, E26, or GU-24 socket; or

9 (c) Is an integrated LED lamp that includes trims and is designed
10 to be retrofitted within existing recessed can housings that contain
11 one of the preceding socket types.

12 (35) "HVAC air filter" means an air-cleaning device used to
13 remove particulate matter from the air and installed in forced-air
14 heating or cooling equipment for a space conditioning or ventilation
15 system.

16 (36) "Deep-dimming fluorescent ballast" means a fluorescent
17 ballast that is capable of operating lamps in dimmed operating modes
18 at any number of levels at or below 50 percent of full output.

19 (37) "Heat-pump water-chilling package" means a factory-made
20 package of one or more compressors, condensers, and evaporators
21 designed for the purpose of heating water. Where this equipment is
22 provided in more than one assembly, the separate assemblies are
23 designed to be used together. The package is specifically designed to
24 make use of the refrigerant cycle to remove heat from an air or water
25 source and to reject the heat to water for heating use. This unit may
26 involve valves to allow for reverse-cycle operation.

27 **Sec. 2.** RCW 19.260.030 and 2009 c 501 s 2 are each amended to
28 read as follows:

29 (1) This chapter applies to the following types of new products
30 sold, offered for sale, or installed in the state:

31 (a) Automatic commercial ice cube machines;

32 (b) Commercial refrigerators and freezers;

33 (c) State-regulated incandescent reflector lamps;

34 (d) Wine chillers designed and sold for use by an individual;

35 (e) Hot water dispensers and mini-tank electric water heaters;

36 (f) Bottle-type water dispensers and point-of-use water
37 dispensers;

38 (g) Pool heaters, residential pool pumps, and portable electric
39 spas;

1 (h) Tub spout diverters; (~~and~~)
2 (i) Commercial hot food holding cabinets;
3 (j) High light output double-ended quartz halogen lamps;
4 (k) Battery charger systems, except those:
5 (i) Used to charge a motor vehicle that is powered by an electric
6 motor drawing current from rechargeable storage batteries, fuel
7 cells, or other portable sources of electrical current, and which may
8 include a nonelectrical source of power designed to charge batteries
9 and components thereof. This exception does not apply to autoettes or
10 electric personal assistive mobility devices, golf carts, and low-
11 speed vehicles, as those vehicles are defined in division 1 of the
12 California Vehicle Code in effect as of the effective date of this
13 section;
14 (ii) That are classified as class II or class III devices for
15 human use under the federal food, drug, and cosmetic act as of the
16 effective date of this section and require United States food and
17 drug administration listing and approval as a medical device;
18 (iii) Used to charge a battery or batteries in an illuminated
19 exit sign;
20 (iv) With input that is three phase of line-to-line three hundred
21 volts root mean square or more and is designed for a stationary power
22 application;
23 (v) That are battery analyzers; or
24 (vi) That are voltage independent or voltage and frequency
25 independent uninterruptible power supplies as defined by the
26 international electrotechnical commission 62040-3 ed.2.0 as of the
27 effective date of this section;
28 (l) Small diameter directional lamps;
29 (m) State-regulated LED lamps;
30 (n) HVAC air filters;
31 (o) Deep-dimming fluorescent ballasts; and
32 (p) Heat-pump water-chilling packages.
33 (2) This chapter applies equally to products whether they are
34 sold, offered for sale, or installed as stand-alone products or as
35 components of other products.
36 (3) This chapter does not apply to:
37 (a) New products manufactured in the state and sold outside the
38 state;

1 (b) New products manufactured outside the state and sold at
 2 wholesale inside the state for final retail sale and installation
 3 outside the state;

4 (c) Products installed in mobile manufactured homes at the time
 5 of construction; or

6 (d) Products designed expressly for installation and use in
 7 recreational vehicles.

8 **Sec. 3.** RCW 19.260.040 and 2009 c 501 s 3 are each amended to
 9 read as follows:

10 The minimum efficiency standards specified in this section apply
 11 to the types of new products set forth in RCW 19.260.030.

12 (1)(a) Automatic commercial ice cube machines must have daily
 13 energy use and daily water use no greater than the applicable values
 14 in the following table:

Equipment type	Type of cooling	Harvest rate (lbs. ice/24 hrs.)	Maximum energy use (kWh/100 lbs.)	Maximum condenser water use (gallons/100 lbs. ice)
Ice-making head	water	<500	7.80 - .0055H	200 - .022H
		>=500<1436	5.58 - .0011H	200 - .022H
		>=1436	4.0	200 - .022H
Ice-making head	air	450	10.26 - .0086H	Not applicable
		>=450	6.89 - .0011H	Not applicable
Remote condensing but not remote compressor	air	<1000	8.85 - .0038	Not applicable
		>=1000	5.10	Not applicable
Remote condensing and remote compressor	air	<934	8.85 - .0038H	Not applicable
		>=934	5.3	Not applicable
Self-contained models	water	<200	11.40 - .0190H	191 - .0315H
		>=200	7.60	191 - .0315H
Self-contained models	air	<175	18.0 - .0469H	Not applicable
		>=175	9.80	Not applicable

33 Where H= harvest rate in pounds per twenty-four hours which must be reported within 5% of the tested value. "Maximum
 34 water use" applies only to water used for the condenser.

(b) For purposes of this section, automatic commercial ice cube machines shall be tested in accordance with the ARI 810-2003 test method as published by the air-conditioning and refrigeration institute. Ice-making heads include all automatic commercial ice cube machines that are not split system ice makers or self-contained models as defined in ARI 810-2003.

(2)(a) Commercial refrigerators and freezers must meet the applicable requirements listed in the following table:

Equipment Type	Doors	Maximum Daily Energy Consumption (kWh)
Reach-in cabinets, pass-through cabinets, and roll-in or roll-through cabinets that are refrigerators	Solid	0.10V+ 2.04
	Transparent	0.12V+ 3.34
Reach-in cabinets, pass-through cabinets, and roll-in or roll-through cabinets that are "pulldown" refrigerators	Transparent	.126V+ 3.51
Reach-in cabinets, pass-through cabinets, and roll-in or roll-through cabinets that are freezers	Solid	0.40V+ 1.38
	Transparent	0.75V+ 4.10
Reach-in cabinets that are refrigerator-freezers with an AV of 5.19 or higher	Solid	0.27AV - 0.71

kWh= kilowatt-hours

V= total volume (ft³)

AV= adjusted volume= [1.63 x freezer volume (ft³)]+ refrigerator volume (ft³)

(b) For purposes of this section, "pulldown" designates products designed to take a fully stocked refrigerator with beverages at 90 degrees Fahrenheit and cool those beverages to a stable temperature of 38 degrees Fahrenheit within 12 hours or less. Daily energy consumption shall be measured in accordance with the American national standards institute/American society of heating, refrigerating and air-conditioning engineers test method 117-2002, except that the back-loading doors of pass-through and roll-through refrigerators and freezers must remain closed throughout the test, and except that the controls of all appliances must be adjusted to obtain the following product temperatures.

Product or compartment type	Integrated average product temperature in degrees Fahrenheit
-----------------------------	--

1	Refrigerator	38±2
2	Freezer	0±2

3 (3)(a) The lamp electrical power input of state-regulated
4 incandescent reflector lamps shall meet the minimum average lamp
5 efficacy requirements for federally regulated incandescent reflector
6 lamps specified in 42 U.S.C. Sec. 6295(i)(1)(A)-(B).

7 (b) The following types of incandescent lamps are exempt from
8 these requirements:

9 (i) Lamps rated at fifty watts or less of the following types: BR
10 30, ER 30, BR 40, and ER 40;

11 (ii) Lamps rated at sixty-five watts of the following types: BR
12 30, BR 40, and ER 40; and

13 (iii) R 20 lamps of forty-five watts or less.

14 (4)(a) Wine chillers designed and sold for use by an individual
15 must meet requirements specified in the California Code of
16 Regulations, Title 20, section 1605.3 in effect as of July 26, 2009.

17 (b) Wine chillers designed and sold for use by an individual
18 shall be tested in accordance with the method specified in the
19 California Code of Regulations, Title 20, section 1604 in effect as
20 of July 26, 2009.

21 (5)(a) The standby energy consumption of bottle-type water
22 dispensers, and point-of-use water dispensers, dispensing both hot
23 and cold water, manufactured on or after January 1, 2010, shall not
24 exceed 1.2 kWh/day.

25 (b) The test method for water dispensers shall be the
26 environmental protection agency energy star program requirements for
27 bottled water coolers version 1.1.

28 (6)(a) The standby energy consumption of hot water dispensers and
29 mini-tank electric water heaters manufactured on or after January 1,
30 2010, shall be not greater than 35 watts.

31 (b) This subsection does not apply to any water heater:

32 (i) That is within the scope of 42 U.S.C. Sec. 6292(a)(4) or
33 6311(1);

34 (ii) That has a rated storage volume of less than 20 gallons; and

35 (iii) For which there is no federal test method applicable to
36 that type of water heater.

37 (c) Hot water dispensers shall be tested in accordance with the
38 method specified in the California Code of Regulations, Title 20,
39 section 1604 in effect as of July 26, 2009.

1 (d) Mini-tank electric water heaters shall be tested in
2 accordance with the method specified in the California Code of
3 Regulations, Title 20, section 1604 in effect as of July 26, 2009.

4 (7) The following standards are established for pool heaters,
5 residential pool pumps, and portable electric spas:

6 (a) Natural gas pool heaters shall not be equipped with constant
7 burning pilots.

8 (b) Residential pool pump motors manufactured on or after January
9 1, 2010, must meet requirements specified in the California Code of
10 Regulations, Title 20, section 1605.3 in effect as of July 26, 2009.

11 (c) Portable electric spas manufactured on or after January 1,
12 2010, must meet requirements specified in the California Code of
13 Regulations, Title 20, section 1605.3 in effect as of July 26, 2009.

14 (d) Portable electric spas must be tested in accordance with the
15 method specified in the California Code of Regulations, Title 20,
16 section 1604 in effect as of July 26, 2009.

17 (8)(a) The leakage rate of tub spout diverters shall be no
18 greater than the applicable requirements shown in the following
19 table:

Appliance	Testing Conditions	Maximum Leakage Rate
		Effective January 1, 2009
	When new	0.01 gpm
Tub spout diverters	After 15,000 cycles of diverting	0.05 gpm

24 (b) Showerhead tub spout diverter combinations shall meet both
25 the federal standard for showerheads established pursuant to 42
26 U.S.C. Sec. 6291 et seq. and the standard for tub spout diverters
27 specified in this section.

28 (9)(a) The idle energy rate of commercial hot food holding
29 cabinets manufactured on or after January 1, 2010, shall be no
30 greater than 40 watts per cubic foot of measured interior volume.

31 (b) The idle energy rate of commercial hot food holding cabinets
32 shall be determined using ANSI/ASTM F2140-01 standard test method for
33 the performance of hot food holding cabinets (test for idle energy
34 rate dry test). Commercial hot food holding cabinet interior volume
35 shall be calculated using straight line segments following the gross
36 interior dimensions of the appliance and using the following
37 equation: Interior height x interior width x interior depth. Interior

1 volume shall not account for racks, air plenums, or other interior
2 parts.

3 (10) The following standards are established for battery charger
4 systems:

5 (a) Large battery charger systems and small battery charger
6 systems manufactured on or after January 1, 2017, must meet
7 requirements specified in the California Code of Regulations, Title
8 20, section 1605 in effect as of the effective date of this section.

9 (b) Battery backup and uninterruptible power supplies that are
10 not consumer products manufactured on or after January 1, 2017, must
11 meet requirements specified in the California Code of Regulations,
12 Title 20, section 1605 in effect as of the effective date of this
13 section.

14 (c) Large battery charger systems and small battery charger
15 systems must be tested in accordance with the method specified in the
16 California Code of Regulations, Title 20, section 1604 in effect as
17 of the effective date of this section.

18 (11) A high light output double-ended quartz halogen lamp must
19 meet minimum efficiency standards of:

20 (a) 27 lumens per watt for lamps with a minimum rated initial
21 lumen value greater than 6,000 and a maximum initial lumen value of
22 15,000; and

23 (b) 34 lumens per watt for lamps with a rated initial lumen value
24 greater than 15,000 and less than 40,000.

25 (12) A small diameter directional lamp must meet minimum
26 efficiency standards of 80 lumens per watt, a power factor of 0.9,
27 and a rated life of 25,000 hours, if manufactured on or after January
28 1, 2017.

29 (13)(a) State-regulated LED lamps must be tested in accordance
30 with the method specified in IES LM-79-08 as published by the
31 illuminating engineering society of North America and must meet the
32 minimum efficiency standards as follows:

<u>Effective date</u>	<u>Minimum lamp efficacy</u>	<u>Minimum color rendering index</u>
<u>January 1, 2017</u>	<u>55 lumens per watt</u>	<u>82</u>
<u>January 1, 2019</u>	<u>65 lumens per watt</u>	<u>84</u>

36 (b) State-regulated LED lamps must have a correlated color
37 temperature that falls within four MacAdam steps of the black-body
38 curve.

1 (c) State-regulated LED lamps that have an ANSI standard lamp
2 shape of A, C, CA, or G must meet the respective omnidirectional
3 light distribution requirements of energy star's product
4 specification for lamps version 1.1.

5 (14) HVAC air filters must be tested in accordance with the
6 methods specified as follows:

<u>Appliance</u>	<u>Appliance performance criteria</u>	<u>Test method</u>
<u>HVAC air filters</u>	<u>Air filter pressure drop</u>	<u>AHRI 680-2009</u>
	<u>Air filter particle size efficiency and</u> <u>MERV</u>	<u>AHRI 680-2009 or ASHRAE</u> <u>52.2-2012</u>
	<u>Dust holding capacity</u>	<u>AHRI 680-2009 or ASHRAE</u> <u>52.2-2012</u>

13 (a) "AHRI" means the air-conditioning, heating, and refrigeration
14 institute.

15 (b) "ASHRAE" means the American society of heating, refrigerating
16 and air conditioning engineers.

17 (c) "MERV" means minimum efficiency reporting value, or the
18 composite particle efficiency metric defined in ASHRAE 52.2-2012.

19 (15)(a) Effective January 1, 2016, deep-dimming fluorescent
20 ballasts must meet the following energy conservation standard in
21 kilowatt-hours per year: Annual energy use $\leq 0.22 \times$ maximum arc power
22 + 18.

23 (b) Deep-dimming fluorescent ballasts must be tested using 10
24 C.F.R. Sec. 430.23(q) (appendix Q1 to subpart B of part 430),
25 modified as follows:

26 (i) The control signal to the ballast must indicate full output.
27 The arc power of all connected lamps must be measured and then added
28 together. This result will be referred to as "max arc power." An
29 appropriate lighting control must be selected to achieve the control
30 signal used to determine the max arc power and to tune the ballast to
31 the appropriate dimming levels. The controls must be selected by
32 using the following methodology:

33 (A) If the ballast manufacturer also manufactures a lighting
34 control designed to be operated with the ballast, the test must be
35 conducted using the ballast manufacturer's lighting control; or

36 (B) If the manufacturer does not manufacture a compatible
37 lighting control, but recommends the use of a specific manufacturer

1 or model of lighting control, the test must be conducted using the
2 recommended lighting controls; or

3 (C) If the manufacturer does not manufacture a compatible
4 lighting control, and does not recommend a specific lighting control,
5 the lab technician shall select a lighting control that sufficiently
6 controls the ballast to complete the test; or

7 (D) If multiple control options are available, use the lighting
8 control that is capable of using all of the features of a ballast and
9 with the minimum amount of other features. The lighting control
10 manufacturer and model number must appear on the test report.

11 (ii) Three sets of input power and arc power must be measured
12 using the federal test procedure with the total arc power tuned to
13 100, 80, and 50 percent of the measured max arc power. If a step
14 dimming ballast or a ballast that can only turn connected lamps on or
15 off has dimming steps other than 80 and 50 percent, then the closest
16 step that is between 90 and including 65 percent must be used for 80
17 percent testing, and the closest step that is between 65 and
18 including 35 must be used for 50 percent testing. If no step exists
19 in the ranges prescribed in this subsection (15)(b)(ii), then no
20 result may be recorded for that percentage dimming test. The
21 resulting input powers must be recorded and referred to as P₁₀₀, P₈₀,
22 and P₅₀.

23 (iii) The ballast must also be tested with a control input set to
24 the lowest dimming state possible up to and including no light
25 output. The input power to the ballast must be measured and recorded
26 as P₀. The measurement must be taken 90 minutes after entering the
27 lowest dimming state possible. P₀ must be recorded as the mean value
28 of measurements taken at 5 second intervals over a 5-minute period.

29 (iv) The annual energy use must be calculated, with the results
30 in kWh/year, using the following formula:

31 Annual energy use = (P₁₀₀ x t₁₀₀ + P₈₀ x t₈₀ + P₅₀ x t₅₀ + P₀ x t₀)/
32 1000

33 Where power is in watts and time values (t_i) are taken from the
34 appropriate tables below:

Time variable	Measurements taken			
	P ₈₀ , P ₅₀	P ₈₀ , No P ₅₀	No P ₈₀ , P ₅₀	No P ₈₀ , No P ₅₀
t ₁₀₀	637	876	1592	2388
t ₈₀	1592	1890	0	0

1	<u>t₅₀</u>	<u>955</u>	<u>0</u>	<u>1592</u>	<u>0</u>
2	<u>t₀</u>	<u>5576</u>	<u>5576</u>	<u>5576</u>	<u>5576</u>

3 (16) Heat-pump water-chilling packages must be tested using ANSI/
4 AHRI 550-590 (I-P) 2011. The heating capacity tests must be conducted
5 at ambient temperatures of each 47 and 17 degrees Fahrenheit and a
6 leaving water temperature of 120 degrees Fahrenheit. If the package
7 is capable of cooling, it must be tested at an ambient temperature of
8 95 degrees Fahrenheit and a leaving water temperature of 44 degrees
9 Fahrenheit.

10 **Sec. 4.** RCW 19.260.050 and 2009 c 501 s 4 are each amended to
11 read as follows:

12 (1) No new commercial refrigerator or freezer or state-regulated
13 incandescent reflector lamp manufactured on or after January 1, 2007,
14 may be sold or offered for sale in the state unless the efficiency of
15 the new product meets or exceeds the efficiency standards set forth
16 in RCW 19.260.040. No new automatic commercial ice cube machine
17 manufactured on or after January 1, 2008, may be sold or offered for
18 sale in the state unless the efficiency of the new product meets or
19 exceeds the efficiency standards set forth in RCW 19.260.040.

20 (2) On or after January 1, 2008, no new commercial refrigerator
21 or freezer or state-regulated incandescent reflector lamp
22 manufactured on or after January 1, 2007, may be installed for
23 compensation in the state unless the efficiency of the new product
24 meets or exceeds the efficiency standards set forth in RCW
25 19.260.040. On or after January 1, 2009, no new automatic commercial
26 ice cube machine manufactured on or after January 1, 2008, may be
27 installed for compensation in the state unless the efficiency of the
28 new product meets or exceeds the efficiency standards set forth in
29 RCW 19.260.040.

30 (3) Standards for state-regulated incandescent reflector lamps
31 are effective on the dates specified in subsections (1) and (2) of
32 this section.

33 (4) The following products, if manufactured on or after January
34 1, 2010, may not be sold or offered in the state unless the
35 efficiency of the new product meets or exceeds the efficiency
36 standards set forth in RCW 19.260.040:

37 (a) Wine chillers designed and sold for use by an individual;

- 1 (b) Hot water dispensers and mini-tank electric water heaters;
- 2 (c) Bottle-type water dispensers and point-of-use water
- 3 dispensers;
- 4 (d) Pool heaters, residential pool pumps, and portable electric
- 5 spas;
- 6 (e) Tub spout diverters; and
- 7 (f) Commercial hot food holding cabinets.

8 (5) The following products, if manufactured on or after January
9 1, 2010, may not be installed for compensation in the state on or
10 after January 1, 2011, unless the efficiency of the new product meets
11 or exceeds the efficiency standards set forth in RCW 19.260.040:

- 12 (a) Wine chillers designed and sold for use by an individual;
- 13 (b) Hot water dispensers and mini-tank electric water heaters;
- 14 (c) Bottle-type water dispensers and point-of-use water
- 15 dispensers;
- 16 (d) Pool heaters, residential pool pumps, and portable electric
- 17 spas;
- 18 (e) Tub spout diverters; and
- 19 (f) Commercial hot food holding cabinets.

20 (6)(a) Large and small battery charger systems, if manufactured
21 on or after January 1, 2017, may not be sold or offered for sale in
22 the state unless the efficiency of the new product meets or exceeds
23 the efficiency standards set forth in RCW 19.260.040.

24 (b) Battery backup and uninterruptible power supplies that are
25 not consumer products, if manufactured on or after January 1, 2017,
26 may not be sold or offered for sale in the state unless the
27 efficiency of the new product meets or exceeds the efficiency
28 standards set forth in RCW 19.260.040.

29 (7) Large and small battery charger systems, if manufactured on
30 or after January 1, 2017, may not be installed for compensation in
31 the state on or after January 1, 2018, unless the efficiency of the
32 new product meets or exceeds the efficiency standards set forth in
33 RCW 19.260.040.

34 (8) A high light output double-ended quartz halogen lamp, if
35 manufactured on or after January 1, 2017, may not be sold or offered
36 for sale in the state unless the efficiency of the new product meets
37 or exceeds the efficiency standards set forth in RCW 19.260.040.

38 (9) A high light output double-ended quartz halogen lamp, if
39 manufactured on or after January 1, 2017, may not be installed for
40 compensation in the state on or after January 1, 2018, unless the

1 efficiency of the new product meets or exceeds the efficiency
2 standards set forth in RCW 19.260.040.

--- END ---